

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Epoxy Resin L 285

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

resin. Binding agent

1.3. Details of the supplier of the safety data sheet

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49 (0)7157 5304-60	Telefax: +49 (0)7157 5304-70
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

1.4. Emergency telephone number: Vergiftungs-Informationen-Zentrale Freiburg
Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Germ cell mutagenicity: Muta. 2

Reproductive toxicity: Repr. 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Suspected of damaging fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

1,2,3-Propantriol, Glycidylether

bis-[4-(2,3-epoxypropoxy)phenyl]propane

Signal word: Warning**Pictograms:**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 2 of 11

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P103	Read label before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P308+P311	IF exposed or concerned: Call a doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
90529-77-4	1,2,3-Propantriol, Glycidylether			50 - 75 %
	292-011-4		01-2119978955-13	
	Muta. 2, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H341 H361fd H302 H315 H319			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			50 - 75 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Where appropriate artificial ventilation. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. Call a physician immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 3 of 11

4.2. Most important symptoms and effects, both acute and delayed

Following eye contact: Headache, Causes tears. Conjunctival redness.

Following inhalation: Suspected of damaging fertility. Suspected of damaging the unborn child.

After skin contact: Irritant, erythema (redness), Suspected of damaging fertility. Suspected of damaging the unborn child.

after ingestion: Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting. Non-flammable. In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂), Hydrogen halide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Collect spillage.

6.3. Methods and material for containment and cleaning up

Stop leak if safe to do so. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation. Avoid contact during pregnancy and while nursing. Avoid release to the environment.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 4 of 11

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against direct sunlight.

7.3. Specific end use(s)

resin. Binding agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Worker DNEL, acute		dermal	systemic	8,3 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	12,3 mg/m ³
Worker DNEL, long-term		dermal	systemic	8,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	12,3 mg/m ³
Consumer DNEL, acute		dermal	systemic	3,6 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	0,75 mg/m ³
Consumer DNEL, acute		oral	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	3,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,75 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,75 mg/kg bw/day

PNEC values

CAS No	Substance	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,013 mg/l
Marine water		0,0003 mg/kg
Marine water (intermittent releases)		0,013 mg/l
Freshwater sediment		0,5 mg/kg
Marine sediment		0,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 5 of 11

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
When using do not eat, drink or smoke. When using do not eat or drink. Avoid contact with eyes and skin. Do not breathe gas/fumes/vapour/spray. Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Wear suitable gloves.

Suitable material:

NBR (Nitrile rubber) (730 Camatril), Butyl caoutchouc (butyl rubber) (898 Butoject)

Breakthrough time (maximum wearing time): ≥ 480 min

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	> 100 °C

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:	not determined
Upper explosion limits:	not determined
Ignition temperature:	not determined

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 6 of 11

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density: 1,140 g/cm³

Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic:
(at 25 °C) 600-900 mPa·s ISO 9371

Viscosity / kinematic: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Odour threshold: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Protect against direct sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂), Hydrogen halide

SECTION 11: Toxicological information

11.1. Information on toxicological effects**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
90529-77-4	1,2,3-Propantriol, Glycidylether				
	oral	LD50 mg/kg	2000	Rat	Manufacturer
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 mg/kg	11400	Rat	Manufacturer

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 7 of 11

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxi)phenyl]propane)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (1,2,3-Propantriol, Glycidylether)
Suspected of damaging fertility. Suspected of damaging the unborn child. (1,2,3-Propantriol, Glycidylether)
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane					
	Acute fish toxicity	LC50	1,3 mg/l	96 h	fish	Manufacturer OECD 203
	Acute crustacea toxicity	EC50	2,1 mg/l	48 h	Daphnia	Manufacturer OECD 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Manufacturer OECD 211

12.2. Persistence and degradability

No information available.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane				
	OECD 301F	5 %	28	Manufacturer	
	Not readily biodegradable (according to OECD criteria)				
	OECD 301B	6 - 12 %	28	Manufacturer	
	Not readily biodegradable (according to OECD criteria)				

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	2,64 - 3,78

BCF

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	3 - 31		

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 8 of 11

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)**14.1. UN number:**

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)**14.1. UN number:**

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)**14.1. UN number:**

UN 3082

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115


Page 9 of 11

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9



Special Provisions: 274, 335, 969

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)


14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9



Special Provisions: A97 A158 A197

Limited quantity Passenger: 30 kg G

Passenger LQ: Y964

Excepted quantity: E1

IATA-packing instructions - Passenger: 964

IATA-max. quantity - Passenger: 450 L

IATA-packing instructions - Cargo: 964

IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: bis-[4-(2,3-epoxipropoxy)phenyl]propane

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 1,2,3-Propantriol, Glycidylether; bis-[4-(2,3-epoxipropoxy)phenyl]propane
 Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment
 (SEVESO III):

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 10 of 11

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 2; H361fd	
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H341 Suspected of causing genetic defects.
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
 H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Revision date: 22.05.2020

Product code: 110115

Page 11 of 11

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)